

# EDDYFI SPYNE

An Ultrafast One-of-a-kind Alternative to PT/MT



# SPECIFICATIONS

## PERFORMANCE

Coverage	200 mm (8 in)
Number of channels required	128
Outer diameter range	150 mm (6 in) OD to flat surfaces
Smallest detectable defects	As small as 2 mm (0.080") L x 1 mm (0.040") D
Max. measurable crack depth	No depth sizing
Scan speed	Up to 600 mm/s (24 in/s) *With full data recording
Lift-off tolerance	Up to 3 mm (0.120 in) *Lift-off compensation to be available **Non-conductive coatings and paints, with monitoring and autocorrection
Materials	All pipeline alloys

## A faster, less operator-dependant, screening than PT/MT

- Very high PoD: leave no crack behind
- Repeatable and reliable results
- Minimal surface preparation required;
- no need to remove coating
- Data archiving
- Compatible with a wide variety of flexible-PCB probes, coils diameters, and topologies



## OTHER FEATURES:

- Grid-As-U-Go™
- Embedded spring-loaded encoder
- Pre-calibration/calibration check tool
- Combined with Magnifi: assisted detection and on-the-spot reporting
- Control buttons for single operator use
- Max. operating temperature: 150 °C (300 °F)



[www.eddyfi.com/spyne](http://www.eddyfi.com/spyne)

The information in this document is accurate as of its publication. Actual products may differ from those presented herein. © 2019 Eddyfi NDT, Inc. Eddyfi, Grid-As-U-Go, Lyft, SmartPULSE, and their associated logos are trademarks or registered trademarks of Eddyfi NDT, Inc. in the United States and/or other countries. Eddyfi Technologies reserves the right to change product offerings and specifications without notice.

[www.eddyfi.com](http://www.eddyfi.com)

[info@eddyfi.com](mailto:info@eddyfi.com)

 **Eddyfi  
Technologies**